

## MATECO®

Paint with mineral matt aspect for indoor

[export@vermillon-deco.com](mailto:export@vermillon-deco.com)

### PRODUCT DESCRIPTION

---

MATECO® is a green paint for indoor use.

MATECO® green paint is eco and health friendly and has a very mineral decorative matt finish. It is solvent free. This water-based paint is easy to apply to various types of surface. It covers well and is economic to use. MATECO® green paint exhibits a very elegant, smooth and opaque finish. Ideal for renovation work as the initial structure is preserved whilst offering a high level of protection.

MATECO® green paint is available in white and is colored using compatible natural pigments or dyes.

Exist in 21 different colors. However custom colors are available on demand and under certain conditions.

### FEATURES

---

- Covers very well and very opaque.
- Rich in mineral fillers: calcium carbonate and titanium oxide.
- Deep matt aspect
- High breathability.
- High permeability to steam.
- Very economic to use.
- Eco and health friendly paint.
- Protects whilst letting the walls breathe, prevents blistering and peeling due to damp.
- Very easy to use.
- Odorless, solvent free, no harmful emissions.

### APPLICATION SURFACES

---

- Coating
- Plaster
- Gypsum plasterboards
- Plaster Tiles
- Cement-based substrates
- Old water-based paints
- Wood and derivatives

## SURFACE PREPARATION

---

Don't forget the preparation, this step is essential to get a perfect result and ensure a better lifetime to the paint. Indoor surfaces should be in conformity with the current standards in force. Surfaces must be clean, dry, and non-friable, without moisture and molds, free of non-adhering parts.

MATECO® green paint can be used on the following materials in areas that are well-ventilated:

- Plaster and derivatives
- Concrete
- cement
- All types of old (well stuck) paint
- Wood and its derivative

All surfaces in wood, plaster and derivatives must be covered with a water-based primer coat (IMPRESSION ACRYLIQUE or IMPRESSION ACRYLIQUE COUVRANTE).

Painted surfaces should first be cleaned and rubbed with sandpaper to make them matt.

For other surfaces please contact us.

## APPLICATION

---

Mix well before applying. Apply with a brush, roller or by spraying, diluted with  $\pm 10\%$  of water. Two coats are better than one. Let dry the first coat before applying the second coat.

Dilute more where necessary according to the means of application and the porosity of the surface.

**Coverage:** 10 m<sup>2</sup> / L per layer, so 5 m<sup>2</sup>/L for 2 Layers.

**Drying:** Out of dust: Dry after 1 to 2hrs. Second coat after 3hrs min, depending on the absorbency of the substrate and the ambient humidity.

**Hardening:** 24h May depends on the temperature.

**Apply at a temperature of:** +5°C to +30°C (40°F or 85°F).

Do not apply to hot or damp surfaces.

Each wall section should be finished the same day. All overlapping should be done in corners or door angles.

Protect the surrounding areas from splashes or clean with water immediately.

## CLEANING

---

Clean tools with water immediately after use.

## STORAGE

---

MATECO® green paint will keep for one year in its original packaging. Keep closed and protect from frost and high temperatures.

## SECURITY PRECAUTIONS

---

Keep out of reach of children.

**Technical Data Sheet:** Please contact us.

Volatile Organic Compounds (VOCs):

- VOC content:

This paint contains few VOC.

Exposure limit value according to Directive n°2010/79/UE: A Class: 30g / L

This product contains max 30g / L.

Water-based product, not subject to labeling.

The information contained in this sheet are the expression of our knowledge and of test results. They can in no case be regarded as bringing a guarantee, or engaging our responsibility in the event of defective application. We recommend making a sample.